

GENERAL DESCRIPTION

Our best professional interior latex primer is formulated to meet the requirements of the construction painter.

SpeedHide Interior primer-sealer is ideal under eggshell and semi-gloss finishes.

This low VOC, low odour paint enables a space to be painted while occupied while delivering the durable product performance required. It provides excellent sealing properties.

Recommended for use on properly prepared interior wallboard and drywall surfaces, wood, and oriented strand board or particle board.

RECOMMENDED SUBSTRATES

Concrete	Gypsum Wallboard
Concrete/Masonry Block	Oriented Strand Board
Particle Board	Wood

CONFORMANCE STANDARDS

- Complies with the Canadian Volatile Organic Compound Concentration Limits for Architectural Coatings Regulations.
- MPI™ approval in category #50, Primer Sealer, Latex, Interior
- Meets MPI Green Performance Standards (GPS-1)
- Meets the Collaborative for High Performance Schools (CHPS) Low-Emitting Materials criteria section 01350

TINTING AND BASE INFORMATION

Refer to the appropriate colour formula book, automatic tinting equipment, and/or computer colour-matching system for colour formulas and tinting instructions.

6-2C White

Some colours, drastic colour changes, or porous substrates may require more than one coat to achieve a uniform finish.

PACKAGING

3.78 L & 18.9 L

PRODUCT DATA

PRODUCT TYPE:	Vinyl-Acrylic Latex
SHEEN:	Flat
VOLUME SOLIDS*:	29% ± 2%
WEIGHT SOLIDS*:	45% ± 2%
VOC*:	< 50 g/L
DENSITY*:	1.3 kg/L

*Product data calculated on product 6-2C.

SPREADING RATE PER COAT: Approximately 37 m² (400 ft²) per 3.78 litres on smooth, nonporous surfaces.

Wet Film Thickness: 102 microns
4.0 mils

Dry Film Thickness: 30 microns
1.2 mils

Coverage figures do not include loss due to surface irregularities and porosity or material losses due to application method or mixing.

DRYING TIME: Dry time @ 25°C (77°F); 50% relative humidity.

To Touch:	30 minutes
To Recoat:	4 hours
Full curing:	14 days

Drying times listed may vary depending on temperature, humidity, film build, colour, and air movement.

Permissible temperatures during the application:

Material:	10 to 32°C	50 to 90°F
Ambient:	10 to 32°C	50 to 90°F
Substrate:	10 to 32°C	50 to 90°F

CLEANUP: Remove as much product quantity as possible and clean tools with lukewarm soapy water immediately after use.

DISPOSAL: Consult your municipality in order to dispose of paint residues according to environmental regulations. Do not pour down a drain or storm sewer.

FLASH POINT: Over 93 °C (200 °F)

FEATURES / BENEFITS

Features

Less than 50 g/L VOC

Fast drying

Excellent sealing properties

Easy application

Soap and water cleanup

MPI approval in Category # 50, Primer Sealer, Latex, Interior

Benefits

Lower than the Canadian Volatile Organic Compound Concentration Limits for Architectural Coatings Regulations.

Same day topcoat turning jobs faster.

Provides a uniform finish.

Can be used by any type of applicator: a high quality brush, roller, paint pad, or by airless spray equipment.

No solvent disposal issues.

Meets strict performance and aesthetic requirements.

LIMITATIONS OF USE

FOR INTERIOR USE ONLY.

PROTECT FROM FREEZING. USE WITH ADEQUATE VENTILATION. **KEEP OUT OF REACH OF CHILDREN.**

Apply only when air, surface and product temperatures are between 10°C to 32°C (50°F to 90°F).

Do not use on floors, in high humidity areas, or on submerged surfaces.

GENERAL SURFACE PREPARATION

Surfaces to be coated must be dry, clean, sound, and free from all contamination including loose and peeling paint, dirt, grease, oil, wax, concrete curing agents and bond breakers, chalk, efflorescence, mildew, rust, product fines, and dust. Remove loose paint, chalk, and efflorescence by wire brushing, scraping, sanding, and/or pressure washing.

Putty all nail holes and caulk all cracks and open seams. Sand all glossy or patched surfaces. Feather back all rough edges to sound surface by sanding.

PRECAUTION: Dry sanding will give rise to dust and/or hazardous fumes. Wear suitable respiratory protective equipment. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Contact a regional Health Canada office for more information.

GYPHUM WALLBOARD: Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust, then prime prior to painting the substrate.

ORIENTED STRAND BOARD: Countersink all nails or screws and putty flush with the surface. Surface should be cleaned to remove any dust or contaminants then primed prior to painting.

PARTICLE BOARD: Countersink all nails or screws and putty flush with the surface. Surface should be cleaned to remove any dust or contaminants then primed prior to painting. Veneered surfaces should be sanded smooth and cleaned to remove any dust or contaminants, before priming the substrate.

WOOD: Unpainted wood or wood in poor condition should be sanded smooth, wiped clean, and then primed. Any knots or resinous areas must be primed before painting.

Countersink all nails or screws, putty flush with surface, then prime.

Before use, be sure to read and follow the instructions and warnings on the label.

Contact your local representative for any additional surface preparation guidelines.

APPLICATION INFORMATION

KEEP OUT OF REACH OF CHILDREN. USE WITH ADEQUATE VENTILATION. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available from your retailer, through our website or by calling 1-800-463-7426.

Stir thoroughly before use and occasionally during use. When using more than one container of the same colour, intermix to ensure colour uniformity.

Application Equipment: Apply with a high quality synthetic brush, roller, paint pad, or by spray equipment. Where necessary, apply a second coat.

Brush: High quality polyester/nylon brush.

Roller: 10 to 20 mm (3/8 – 3/4 in.) nap synthetic roller cover.

Airless Spray: Pressure 2000 psi, tip 0.015 in. - 0.021 in.

Spray equipment must be handled with due care and in accordance with the manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

Thinning: Do not thin.

PRECAUTIONS

Keep out of the reach of children. Keep containers tightly closed and sealed until ready for use. Before using the products listed in this publication, carefully read each product label and follow directions for its use. Use personal protective equipment as required. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation.

MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE AND SKIN IRRITATION. Avoid breathing vapours, spray or mists. Avoid contact with skin and eyes. Wear protective gloves/clothing and eye/face protection.

FIRST AID: If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call poison centre or doctor/physician. For workplace use, an SDS are available from your retailer, through our website or by calling 1 800 463-7426.

EMERGENCY SPILL INFORMATION: 1 514 645-1320 or 1 800 463-7426.

LIMITED WARRANTY

PPG Architectural Coatings Canada, Inc. warrants performance of its products to its intended use if properly applied in accordance with the label directions and the specifications of the technical data sheet. Having no control over the application methods and conditions or the circumstances related to its use, no other warranty, expressed or implied, statutory or otherwise is given. This limited warranty extends only to the original purchaser of the product and is not transferable or assignable. If the product fails to conform to this limited warranty, we will, at your option, furnish replacement product or refund the purchase price. This limited warranty excludes (1) labour or costs of labour for the application or removal of any product and (2) all other direct, indirect, incidental, special or consequential damages.

The PPG Paints is a registered trademark of PPG Industries Ohio, Inc. SpeedHide is a registered trademark of PPG Architectural Finishes, Inc. MPI is trademark of Master Painters Institute, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate: however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-866-660-2220.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.ppgpaints.com

PPG Architectural Coatings Canada Inc.
2505, de la Metropole
Longueuil, QC, Canada, J4G 1E5

Technical Services	450 442-2220	
	1 866 660-2220	Architect/Specifier
Fax:	450 679-8893	1-888-PPG-IDEA
	1 800 278-8893	