



Cloverdale Paint

SPECIALTY COATINGS



**INTERIOR / EXTERIOR
CLEAR REPELLANT
SEALERS**

#43700 AQUASEAL
WATERBORNE CLEAR
ACRYLIC SEALER

#45110 CONCRETE GLAZE
SOLVENT BASED ACRYLIC
SEAL 'N' SHINE

AQUASEAL #43700 / CONCRETE GLAZE #45110

AQUASEAL TECHNICAL SPECIFICATIONS

INTENDED USES

AquaSeal Clear Acrylic Water Repellent is a premium quality clear interior/exterior waterproofing sealer that penetrates dry, porous materials such as wood, masonry and stucco establishing a moisture barrier to keep water out. AquaSeal provides positive moisture protection to all types of woods including: redwood, cedar, pine, fir, plywood and pressure treated lumber. This product will also waterproof and protect concrete, brick, concrete block and masonry from moisture damage caused by freeze-thaw cycles. AquaSeal may also be used on canvas such as patio umbrellas, awnings and camper canvas. AquaSeal is nonflammable and very easy to use.

CERTIFICATIONS

MPI #99
Environment Canada VOC
LEED® Compliant. Qualifies for LEED® Credit Points.

BASES AVAILABLE

N/A

V.O.C.

Less than 300 g/L

SOLIDS

10% by volume
11% by weight

FILM THICKNESS (per coat)

Wet: 5.0 - 16 mils (125 - 400 microns)
Dry: 0.5 - 1.6 mils (13 - 40 microns)

VISCOSITY

23 - 28 secs Ford Cup #4

DRY TIME

Tack Free: 30 minutes
Hard Dry: 2 - 4 hours

SPREAD / COVERAGE

100 - 300 ft²/gal (2.5 - 7.5 m²/L)

TOOLS & TECHNIQUES

Brush, roller or spray

CLEAN UP

Clean tools and equipment with warm, soapy water. Contact your local municipality for disposal instructions.

CONCRETE GLAZE TECHNICAL SPECIFICATIONS

INTENDED USES

Recommended as a sealer for concrete, concrete block or exposed aggregate driveways pathways or steps. Also ideal for stamped concrete patios or paving stones. Use indoors on slate, tile or terrazzo. Ventilate well for interior use and remove all possible sources of ignition.

CERTIFICATIONS

MPI #34 and #104
Environment Canada VOC

BASES AVAILABLE

N/A

V.O.C.

Less than 400 g/L

SOLIDS

21.5% by volume
27% by weight

FILM THICKNESS (per coat)

Wet: 3.2 - 5.3 mils (80 - 133 microns)
Dry: 0.7 - 1.1 mils (18 - 28 microns)

VISCOSITY

20 - 30 #4 Ford Cup

DRY TIME

Tack Free: 30 Minutes
Hard Dry: 1 Hour

SPREAD / COVERAGE

300 - 500 ft²/gal (7.4 - 12.3 m²/L)

TOOLS & TECHNIQUES

Brush, roller or spray

CLEAN UP

Clean tools and equipment with 78011 Xylene. Contact your local municipality for disposal instructions.

AquaSeal Clear Acrylic Water Repellent

AquaSeal Clear Acrylic Water Repellent is a premium quality all-purpose sealer for use on a variety of surfaces. AquaSeal forms an invisible weather resistant, moisture barrier protecting a variety of substrates to keep water out. Can be used for interior or exterior application. Approved by the Master Painter's Institute under category #99.

Clear Concrete Glaze

Seal 'n Shine is a solvent based acrylic penetrating sealer for concrete, brick, exposed aggregate, tile, mortar and masonry block. This product will protect concrete and masonry surfaces from spalling, efflorescence, de-icing salts, oils, grease and freeze-thaw damage. The film will show some sheen depending on the porosity. It is very clear, non-yellowing, abrasion resistant, non-lifting and is suitable for interior or exterior exposure. This product is VOC compliant under Environment Canada regulations and is approved by the Master Painters Institute under category # 34 & 104.

Use extreme caution when applying indoors to remove all possible sources of ignition such as pilot lights, etc.

LEED® is a registered trade mark of U.S. Green Building Council

MANUFACTURED BY



Cloverdale Paint

6950 King George Boulevard
Surrey, BC, Canada
V3W 4Z1
www.cloverdalepaint.com

Cloverdale Paint stores and authorized dealers