

Liquid Rubber Cool Foot Coating is a brush, roll and spray high-performance, acrylic, elastomeric coating that reduces heat transfer by up to 35% compared to regular paint. The Cool Foot Coating cures into a durable, seamless, colored waterproof membrane.

Liquid Rubber Cool Foot Coating contains no solvents, is non-toxic, VOC-free, and is non-flammable. The cured membrane has excellent solar reflectivity and UV stability and it can be applied on its own or in combination with Liquid Rubber Seam Tape to provide a dependable protective, waterproof solution.

Liquid Rubber Cool Foot Coating Performance Features

- Reduce Heat Transfer by up to 35%
- Excellent solar reflectivity and emissivity
- No solvents, non-toxic and VOC-Free
- UV resistance
- Seamless membrane
- Easy to apply
- No Tackiness
- Color options available

Application Equipment

Liquid Rubber Cool Foot Coating is applied using a brush, roller or paint sprayer to provide a seamless and fully adhered membrane to most substrates. This unique sealant is designed as a stand-alone coating and can be applied with Liquid Rubber Seam Tape. Cool Foot Coating should be applied at a coverage of 100 ft² / G per coat. Min 2 coats.

Drying Time

At 25°C and 50% relative humidity, the Cool Foot Coating fully cures in 24-48 hours. Curing time increases in colder temperatures or higher humidity so environmental conditions must be considered before application.

Suitable Applications include but are not limited to:

- Wood, Concrete, Decks, Docks, Walls, Fences

Physical Properties

Color (Liquid)	Colors Available	Water Absorption (EN 1062)	0.004 kg/m ² -hr ^{0.5}
% solids (V/V) (Liquid)	55-65%	Accelerated Weathering	N/A
Tensile strength	>500 psi	Durometer Hardness	85 Shore A
Elongation	>50%	Working Temp Range	-40°C to +40°C

Limitations & Warranty

- Do not apply to dirty or contaminated surfaces
- Do not apply below 10°C
- Avoid contact with solvents and solvent type adhesives

Packaging

- 205 litre plastic drum (55 Gal)
- 18.9 litre pail (5 Gal)
- 3.78 litre can (1 Gal)

The information contained herein is the best available to Liquid Rubber Canada Inc. and its affiliated companies relating to Liquid Rubber products and the use of Liquid Rubber products. It is based on tests believed to be reliable. There is no warranty expressed or implied in association with product use. Liquid Rubber Worldwide Inc. assumes no liability for any damages incurred in association with the use of Liquid Rubber Canada Inc. products. Information is subject to change without notice.