

Liquid Rubber Multi-Purpose Primer is a high performance, engineered bonding aid formulated to improve the adhesion of Liquid Rubber membranes to a variety of substrates. Liquid Rubber Multi-Purpose Primer is a single component composition suitable for easy and safe application to numerous surfaces including concrete, wood, high-density polyethylene and EPDM, by means of brush, rollers or spray equipment.

Liquid Rubber A-Primer Performance Features

- Non-toxic, no VOC's and no solvents
- Clear or grey color
- Fast Drying
- Highly adhesive to EPDM & Concrete
- Freeze/thaw stable
- High Coverage Rate

Application Equipment

Liquid Rubber A-Primer may be applied as a single component system using either manual or spray application methods. Manual application can be carried out using conventional brush or roller equipment, or alternately the product may be sprayed using a delivery system and nozzles appropriate for the viscosity of this material.

The recommended coating thickness of the Multi-Purpose Primer is between 4-5 mils DFT (.01 mm). For best results, the Multi-Purpose Primer should be applied to a dry surface that is free of dirt, debris, oil and grease. Application immediately before the onset of rain is not recommended.

Drying Time

Curing time will vary depending on temperature and relative humidity. Typically, A-Primer will be dry to the touch, and ready for top coating within 5-10 minutes at 20°C (50% RH).

Suitable Applications include but are not limited to:

- EPDM & TPO
- Wood
- HDPE & Concrete

Physical Properties

Color (Liquid)	Clear
% solids (wt) (Liquid)	40%
Viscosity	50 CPs

Adhesion to EPDM ASTM C-794	3.0 psi
Low Temp Flex	-45C
Working Temp Range	-45C to +80C

Limitations & Warranty

- Do not apply to dirty or contaminated surfaces
- Do not apply below 10°C
- Avoid contact with solvents and solvent type adhesives

Packaging

- 205 L plastic drum (55 Gal)
- 18.9 L pail (5 Gal)
- 3.78 L can (1 Gal) or 946 ml can (1 Quart)

The information contained herein is the best available to Liquid Rubber Worldwide Inc. and its affiliated companies relating to Liquid Rubber products and the use of Liquid Rubber products. It is based on tests believed to be reliable. There is no warranty expressed or implied in association with product use. Liquid Rubber Worldwide Inc. assumes no liability for any damages incurred in association with the use of Liquid Rubber Worldwide Inc. products. Information is subject to change without notice.